

SERIES **GL-GLR**



TECHNICAL FEATURES - CARACTERISTICAS TECHNICAL TECHNISCHE DATEN - CARACTERISTIQUES TECHNIQUES - CARATTERISTICHE TECNICHE

| <i>Pump type Tipo de bomba Pumptyp Type de pompe Tipo pompa</i> | Code Codigo Kodex Code Codice | Output Caudal Leistung Débit Portata | | Pressure Presion Druck Pressione Pressione | | Power Potencia Leistung Puissance Potenza | | RPM Rev./1' U.P.M. Tours/1' N° giri/1' | Weight Poids Gewicht Peso Peso | Oil Aceite Öl Huile Olio | Head Presion de agua Forderdruck charge d'eau Battente | |
|---|---|--|------------|--|------------|---|-----------|--|--|--------------------------------------|--|------------|
| | | <i>l/min</i> | <i>gpm</i> | <i>bar</i> | <i>psi</i> | <i>hp</i> | <i>kw</i> | | | | <i>bar</i> | <i>psi</i> |
| GL 92/300 | 911001 | 92 | 24,3 | 300 | 4350 | 73 | 54 | 750 | 150 | 10,0 | max 3 | max 43,5 |
| GL 109/260 | 911002 | 109 | 28,8 | 260 | 3770 | 75 | 55 | 750 | 150 | 10,0 | max 3 | max 43,5 |
| GL 135/210 | 911003 | 135 | 35,7 | 210 | 3045 | 75 | 55 | 750 | 150 | 10,0 | max 3 | max 43,5 |
| GL 171/160 | 911004 | 171 | 45,2 | 160 | 2320 | 73 | 54 | 750 | 150 | 10,0 | max 3 | max 43,5 |
| GL 212/130 | 911005 | 212 | 56,1 | 130 | 1885 | 73 | 54 | 750 | 150 | 10,0 | max 3 | max 43,5 |
| GL 256/110 | 911006 | 256 | 67,6 | 110 | 1595 | 75 | 55 | 750 | 150 | 10,0 | max 3 | max 43,5 |
| GLR 92/300 | 911007 | 92 | 24,3 | 300 | 4350 | 73 | 54 | 1500 | 175 | 11,0 | max 3 | max 43,5 |
| GLR 109/260 | 911008 | 109 | 28,8 | 260 | 3770 | 75 | 55 | 1500 | 175 | 11,0 | max 3 | max 43,5 |
| GLR 135/210 | 911009 | 135 | 35,7 | 210 | 3045 | 75 | 55 | 1500 | 175 | 11,0 | max 3 | max 43,5 |
| GLR 171/160 | 911010 | 171 | 45,2 | 160 | 2320 | 73 | 54 | 1500 | 175 | 11,0 | max 3 | max 43,5 |
| GLR 212/130 | 911011 | 212 | 56,1 | 130 | 1885 | 73 | 54 | 1500 | 175 | 11,0 | max 3 | max 43,5 |
| GLR 256/110 | 911012 | 256 | 67,6 | 110 | 1595 | 75 | 55 | 1500 | 175 | 11,0 | max 3 | max 43,5 |
| GLR 92/300 | 911013 | 92 | 24,3 | 300 | 4350 | 73 | 54 | 1800 | 175 | 11,0 | max 3 | max 43,5 |
| GLR 109/260 | 911014 | 109 | 28,8 | 260 | 3770 | 75 | 55 | 1800 | 175 | 11,0 | max 3 | max 43,5 |
| GLR 135/210 | 911015 | 135 | 35,7 | 210 | 3045 | 75 | 55 | 1800 | 175 | 11,0 | max 3 | max 43,5 |
| GLR 171/160 | 911016 | 171 | 45,2 | 160 | 2320 | 73 | 54 | 1800 | 175 | 11,0 | max 3 | max 43,5 |
| GLR 212/130 | 911017 | 212 | 56,1 | 130 | 1885 | 73 | 54 | 1800 | 175 | 11,0 | max 3 | max 43,5 |
| GLR 256/110 | 911018 | 256 | 67,6 | 110 | 1595 | 75 | 55 | 1800 | 175 | 11,0 | max 3 | max 43,5 |